

WASTE TREATMENT REPORT

The following is the data obtained on the water flow, BOD and solids losses from the mill for the period of July 9, 1965 to September 15, 1965. The figures are reported in three parts to cover changes made in the operation of the pilot plant.

	7/9-19/65		7/20-8/15	8/16-9/15	Ave.
Primary Water Flow	1,397,000	G.	1,325,000 G	1,450,000	G. 1,391,000
Secondary Water Flow	129,000		83,500	89,000	
T.S.S. Primary Influent	12,425	#	13,850 #	12,400 #	12,692
T.S.S. Primary Effluent	1,645		2,460	2,180	2,095
T.S.S. Secondary Influent	138		146	126	,
T.S.S. Secondary Effluent	83		136	94	
BOD Primary Influent	2,556	#	3,407 #	3,520 #	3,161
BOD Primary Effluent	1,491		2,321	2,870	2,277
BOD Secondary Influent	122.6		172.0	248.0	
BOD Secondary Effluent	40.7		20.7	16.4	
% EFF. Secondary	67		88	93	
Lbs. Ammonia	375		187.5	37.1	
Lbs. Phos. Acid	. 49		24.5	. 7.8	

The 129,000 Gal. flow exhausted the oxygen supply in the aeration pit too rapidly so the volume was cut. We were given an erroneous nitrogen phosphurous EOD ratio. The reduced amount of nutrients did not hurt the efficiency of the system.



An average of a weeks tests on the sewers going to the river are listed below.

•	#2 Sewer	Boiler House Sewer
Water Flow	1,115,000	525,000
BOD Lbs.	2,300	. 440
T.S.S. Lbs	8,436	2,873

The chief negative factors are the high influent solids to the primary tank and untreated water loss, both in fiber and BOD through the #2 and Boiler House Sewer.

In regard to the high influent solids to the settling tank, it is felt that this is due in great part to the increase of losses through the Savealls. For instance, the total suspended solid content of the clear water discharge was .83 lbs per thousand gallons on #4 and approx. .90 lbs. per thousand gallons on #3 a year, as against 1.64 and 13.3 respectively at present. It is difficult to estimate the effect of the correction of this condition but it should result in a solids to the clarifier of 5300 per day and an effluent of 550 per day. The 200 should be about 1960 lbs. going in and 1360 coming out.

As stated in a previous report, the treatment system does an adequate job on the waste brought to it, but the untreated loss through the other sewers is excessive due to losses from the water through the old storm sewer and through the boiler house sewer from the Materials Preparation Department. We also discharge the new #2 Saveall to the river.

the understand that it is proposed to divert the fresh water now discharging from the coater hot water tank from the coater sewer to the fresh water sump in the coater section. The coater losses will go into the old storm sewer as usual but this will be diverted into the white



water sewer controlled by the diversion valve in the #3 system. It is also proposed to move the #2 Saveall discharge to this line. The materials preparation losses are to be sumped and possibly be discharged into the coater sewer. In regard to this, it is suggested we consider sumping the boiler blowdown and running it into the storm sewer line instead.

If these steps are successful, this will bring up to 2,740 lbs. more BOD and 11,209 of suspended solids into the primary clarifier. This should result in about 3300 lbs. BOD and 3,595 lbs. of solid from the tank.

The secondary system can be expanded by the use of a mechanical aerator to treat 300,000 gallons of primary discharge. This, based on present discharge concentrations, would be 832 lbs. treated and 663 lbs. removed figuring 80% efficiency. This would leave 2,005 BOD going to the sewer, which is too much, as the amount stipulated is 2,260 lbs. of BOD.

The d.

J. A. Dean

5



WATER LUSS POINTS

#2 MACHINE

LC CATION

- 1-3 Calender Air and Reel Cooling
- L Size Press Floor Drain
- 5 Drver Control Drain
- 6 Stickle Condensate Fump Drain
- 7 Floor Drain
- 8 Press Pit--Fibrous
- Suction Seal--Fibrous
- 10 Wire Section Floor Drain--Fibrous
- 11 • • • •
- 12 Suction Seal--Fibrous
- 13 Alum Pump Area Flush Hose

#3 MACHINE

- 1 Reel Drum Cooling
- 2 Calender air Cooling
- 3 Duster Roll Cooling
- 4 Size Press Floor Drain
- Compressor Cooling
- 6 Condenser Cooling
- 7 Condensate Pump Cooling
- 8 Oil System Pump Cooling
- 9 Suction Seal Water
- 1-0 Go to Clear Water Sewer--River
- 10 Pross Pit
- 11 Suction Seal
 12 Floor Drain
- 10-12 To Settling Tank or River

#4 SIDE-CLEAR MAIDR SEVER

- 1 Cleaner Boll Cooling
- 2 Compressor Cooling
- 3 Suction Seal (Fibrous)
- 1-3 Joined with #3 Fresh Water And Most Goes into #L Tank Sewer

#4 SIDE-TANK SEFER

- 1 Condensor Cooling
- 2 Size Press Floor Drain
- 3 Turbine Cooling

- 6 Suction Seal

The same of the same of the same	m &	Identification number	industry	State	Res	or Basin			L		
ver call	F P				İ						
TEM 1	FRESH	WATER FROM — —	<u></u>		· · · · · · · · · · · · · · · · · · ·			of gailons e year	T		
VATER									\dashv		
ITAKE Y KIND	A. Pu	blic water system (municipally a	or privately owned)		*		1 1	ր-ր	+		
ND DURCE:	B. Co	mpany surface water system, so	uch as streams or lakes						\dashv		
964	c . c	986	4.6								
	D.	100	c.8								
	BRACK			٦							
	E. Ox	pean, ponds, wells, etc. (Brackis are than 1,000 parts per million	h water is defined as all water of dissolved solids)	with			_				
	F.		OTAL WATER INTAKE				100	9.0			
EM 2				- d/ail-1			32	320.9			
URPOSE	A	ocess (all water that comes dire	serily in conject with products a	ng/or morerios)					_		
of Water NTAKE:	B. Ca	soling and condensing for steam	1 electric power generation				28	0.8			
964	<u>c</u> 0	ther cooling and condensing (in	cluding air-conditioning)				33	0.3	_		
	D. Bo	piler feed, sanitary service, and	other uses				6	8.8			
			TAL INSTARCE	anual itan 18)			100	n.8			
TEM 3		as any water recirculated or			2 🗆 N	0	1 200	0.0	ヿ		
VATER	B. If	"Yes," report estimated total gi	uantity of water which would t	rave been							
ECIRCULA-		quired if no water was recircula					164	1.8			
ION AND EUSE:	c 0	neck each purpose for which we	ater was recirculated or reused	:							
964	l		<u></u>					n ·			
	1.	Process	x	3. Other co	ooling and	condensing (including	air-conditioni	ing)			
	2.	Condensing water for steam el power generation		4. Boiler fe	ed, sanita	ry service, and other	U ses	🔭 🔻			
TEM 4											
MATER	Report	water discharged, whether trea	sed or not. Exclude water evo	porated or otherwise can	svimed an	d ner brought to utim		pont. or freated p	rier		
XS- CHARGED:	Point of discharge Key Milliens of gallons for the year						to discharge (Check applicable be				
						,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	None	Some			
	A R	ablic utility sower (publicly or p	rivately owned)				15	3	4		
					3-1		1		(
		efore united books feterage. John				076_0 -	2	3 🔻	4		
		rface water body (stream, lake,			3-2	976.9	2 2	3 X 3	4		
		rface water bady (stream, lake, round (wells, spray, etc.)				976.9	2 2	-	4		
	c G	round (wells, spray, etc.)	ocean, etc.)		3-2	976.9	2 2 2	X 3	4-		
	c G	round (wells, spray, etc.) ansferred to other users (after t	rse in your addablishment)		3-2		2 2 2	-	4		
TEM S	C. G. D. Tr	round (wells, spray, etc.) ansferred to other users (after t	use in your establishment) OTAL WATER BRICHARGED— In et A. B. C. and D)	chlorination only:	3-2	976.9	2	X 3	4		
	C. G. D. Tr	round (wells, spray, etc.) ansferred to other users (after users (included in item 1))	use in your establishment) OTAL WATER BRICHARGED— In et A. B. C. and D)	chlorination only:	3-2		2 2 3 3-1:	X 3	4		
WATER	C. G. D. To E. A. In	round (wells, spray, etc.) ansferred to other users (after users (included in item 1))	use in your establishment) TAL WATER BUILDHARGED— In of A. C. C. and D) Treated prior to use except by	chlorination only:	3-2		2	X 3	4		
VATER	C. G. D. Tr. S. A. Int.	round (wells, spray, etc.) ansferred to other users (after users (afte	use in your establishment) TAL WATER BUILDHARGED— In of A. C. C. and D) Treated prior to use except by	chlorination only:	3-2		2 2 3 3-1:	X 3	4		
VATER REATED Include Imple as Include as Inc	C. G. D. Tr. S. A. Int.	round (wells, spray, etc.) ansferred to other users (after users (afte	use in your establishment) TAL WATER BUILDHARGED— In of A. C. C. and D) Treated prior to use except by		3-2 3-3 3-4*	976.9	2 2 3 3-1:	X 3	4		
VATER REATED Include Imple os Include os Include Inclu	C. G. D. Tr. S. A. Int.	round (wells, spray, etc.) ansferred to other users (after users (aft	rse in your establishment) TTAL WASER EMICHANGED— or of A. E. C. and D) treated prior to use except by If gallons for the year]	rg honge	3-2	976 • 9	2 2 3 3-1:	X 3	4		
/ATER REATED Include Imple as off as omplex actment);	C. G. D. Tr. S. A. Int.	round (wells, spray, etc.) ansferred to other users (after users (afte	se in your establishment) TTAL WASE BECARGED— in of A. C. said D) treated prior to use except by f gallons for the year)	rg honge	3-2	976 » 9	2 2 3 3-1:	X 3	4		
/ATER REATED Include Imple os ell os omplex eatment):	C. G. B. Tr. S. A. In:	round (wells, spray, etc.) ansferred to other users (after users (aft	ise in your establishment) PTAL WATER BESCHARGED— IN of A. B. C. and D) treated prior to use except by If gallons for the year)	ng hange an control	3-2	976 • 9	2 2 3 3-1:	X 3	4		
VATER REATED Include Imple os Include os Include Inclu	C. G. D. Tel E. A. Ini 1. 2.	round (wells, spray, etc.) ansferred to other users (after y TO (54) take water (included in item 1) AMOUNT TREATED (millions a Check methods of treatment: 301 Aeration 302 Coagulation 503 Filtration	ise in your establishment) STAL WASER SECRATORD— in of A. C. and D) treated prior to use except by If gallons for the year)	ng hange an control	3-2	976 • 9	2 2 3 3-1;	X 3	4		
VATER REATED Include Imple os Include os Include Inclu	C. G. B. W. 1.	round (wells, spray, etc.) ansferred to other users (after users (afte	ise in your establishment) PTAL WATER BESCHARGED— In of A & C and D) treated prior to use except by If gallons for the year)	ng hange an control	3-2	976 • 9	2 2 3 3-1;	X 3	4		
VATER REATED	C. G. B. W. 1.	round (wells, spray, etc.) ansferred to other users (after users (aft	ise in your astablishment) PTAL WATER BISCHARGED— IN of A. B. C. and D) treated prior to use except by If gallons for the year) \$\begin{align*}	ng hongs on control recirculation or rouse?	3-2 3-3 3-40 5-6	976.9	2 2 3 3-1;	X 3	4		
VATER	C. G. B. W. 1.	round (wells, spray, etc.) ansferred to other users (after users (aft	ise in your establishment) TTAL WASER ENCHARGED— In of A. C. and D) treated prior to use except by If gallons for the year)	ng honge an control recirculation or rouse?	3-2 3-3 3-40 3-6	976,9 Other (Speally): 97 Other (Speally): 17	2 2 3 3-1;	X 3			
VATER REATED Include Imple os Include os Include Inclu	C. G. B. W. 1.	round (wells, spray, etc.) ansferred to other users (after users users users (after users u	ise in your actablishment) PTAL WASE BUCHARGED— In al. A. C. and D) treated prior to use except by If gallons for the year)	ng hange an control rectrculation or rouse?	3-2 3-3 3-40 3-6	976 s 9 Other Cheatly: OT	2 2 3 3-1;	X 3			

1	D.	•		rech wester A. B. and C				***************************************	_					->		1000	3.8		14
	BRACKISH (SALT) WATER FROM — —																		
ι	E. Ocean, panils, wells, etc. (Brackish water is defined as all water with more than 1:000 parts per million of dissolved solids)								••••				1-5						
	F. Sup of D and D										1.000	0.8		1-6					
12	A. Process (all water that comes directly in contect with products and/or materials)										320	0.9		2-1					
POSE NATER	B. Cooling and condensing for steam electric power generation										280	3.8		2-2					
NCE:											330	0.3		2-3					
•	C. Other cooling and condensing (including air-conditioning)												8.8						
		D. Bailer feed, sanitary service, and other uses TOTAL INTAKE									1000-8				1-40				
13	E.	Was any	water red	() Ireulated a	he sum of A.	B, C, and	D should eq	raficam Ti	"		2	No	.)		100040				3-4
TER . RCULA- 1 AND SE:	A. Was any water redirectated at recised?								1611.8				2-7						
		2. Conde	sing water	for steam e	lectric	1	x				-		indensing (in	•			ין	I	
14	Rep	ort water o	lischarged,	whether tre	sted or not.	Exclude w	ater evapor	sted or of	her	wise con	numed	and n	et brought h	o ultima	e disc			ed prior	
rer .rged: 4		Point of discharge Key Millions of gallon for the year								- 7	All								
	A.	Public uti	lity sewer (publicly or p	crivately ow	ned)					3-1				2		3	4	
	8.	B. Surface water body (stream, lake, ocean, etc.)							3-2		976.9		2	,	3 X	4			
	c									2		3	4						
										2		3	4						
		Tronsigni	10 011161	T	DTAL WAT	n enchia				->			976.9				1	-	- 4
4.5	E.	Intake wa	iter (includi	(3 (d in item 1	um of A, B, treated price		ecept by chi	orination o	only		3-6	<u> </u>	710.7		<u> </u>			<u> </u>	. ***
TER .																			,
ATED Jde				D (millions	of gallons fo	or the year)			• •		• • • • •					1.0			4-1
le as as		2. Check	methods of	treatment:															4-2
ment):	501 Agration																		
4		502 Coogulation												-					
	8.	Was it no	icossery to	treat wate	or reported	in item 3	prior to rec	irculation	07	reuse?									4-3
		1. 🗀 Ye	15	2.	No No														7-7
		3. If "Ye	s," check m	ethods of tr	ealment:														
	511 Aeration 514 Softening Other (Specify):																		
	512 Coagulation													-					
	C.	Water (in	cluded in it	em 4E) treat	ed prior to				_										
															Γ.				
	-	1. AMOU	NT TREATE	D (millions)	of gallons fo	or the year)			٠.,	•••••		• • • •	· • • · · · · • •		<u> 4</u>	56.0			6-4
		2. Check	methods of	treatment:															4-5
	☐ 521 Coagulation ☐ 524 Trickling filters ☐ 527 Ponds or lagoons ☐ 522 Primary settling ☐ 525 Activated sludge Other (Specify):									oons									
			Secondary				Digestion					528		7			-	725	-
FOR CENS		Key 4-6	0	3A	3¢1	3C2	30	3C4	1			<u> </u>	48	40		4D	-+	581/	3 44

WC-D-13 (1-15-65)

AT SERVICE OF LESSONS TO

The second is the larger to provide the second seco

(Please correct if page or address has been changed

INDUSTRIAL WATER USE IN 1964

Please complete and return this form to the Bureau of the Census, Washington, D.C., 20233, net letter than 36 days after you receive it. A return envelope is enclosed. Retain one capy of the form for your files.

BOTOUS 0025 4 26211 340031707 HAMILTON PAPER CO HICHEGAN DIVISION 111 MELL ST PLAINMELL 000 AICH

YOUR PILE COPY

INSTRUCTIONS

General — Report all quantities in millions of gallons for the year. Do not report in gallons per minute or gallons per day. If the quantity is 5,600,000 gallons for the year, report as 5.6_1 if it is 600,000 gallons for the year, report as 0.6_2 if it is 80,000 gallons for the year, report as 0.08. If no water is used, treated, or discharged, report "None." Reasonably accurate estimates are acceptable.

ITEM 1 - Water intake by kind and source.

A. Include fresh water supplied by a water system (whether publicly or privately awned) whose primary purpose is the supply of water to the general public, include also fresh water supplied by systems whose principal function is the supply of water to industrial users.

B and C. Include frash water obtained from your own water supply system and frash water obtained from another company where the supplying company is not primarily a water supplier to the general public and/or industrial users, include only your own portion of fresh water obtained from a joint water supply system operated by your company.

E. Report total intake of brackish water (as defined) regardless of source.

ITEM 2 - Self-explanatory

ITEM 3 - Water recirculation and revee.

Report the total quantity of water which would have been needed if no water was recirculated or reused. For example, if 100 million gallons of intake water

were used twice for cooling purposes, and then the same water was again reused for washing products or materials, the total water required figure would be 300 million gallans (less coreumption and evaporation loss).

ITEM 4 - Water discharged.

Include all water brought to ultimate discharge point for your establishment. Do not include water held in your ponds, lagoons, or basins, for rouse or treatment, until actually discharged. Do not report water discharged by evaporation.

A and B - (Self-explanatory).

C. Ground — include seepage into ground from your holding pands, laguens, etc. (Note: If water is transferred to an agricultural establishment for spray irrigation, report such quantity in 4D).

D. Transferred to other users - include transfers after your own use, to enother establishment of either your company or another company.

HENDEL Water Manuel.

Report the total quantity of water treated for control or biological growth, removal of suspended or dissolved solids, for corresion centrol, or for any other purpose by simple or complex methods. From 5A, exclude water intelled treated only by ablantation. In 5C, include water treated for discharge by chlorination as well as by other methods. In each section of item 5[A, B, and C], check all applicable methods of treatment.

Remarks:

HAMILTON PAPER CO MICHIGAN DIVISION 111 MILL ST PLAINMELL

000

HICH

Please complete and return this form to the Burgau of the Ceneus, Washington, D.C., 1921, and Salar Shim 20 days after you receive it. A return etriclope is anclosed. Season are sayly of the farm for your film.

YOUR FILE COPY

INSTRUCTIONS

General — Report all quantities in millions of gallons for the year. Do not report in gallons per minute or gallons per day. If the quantity is 5,400,000 gallons for the year, report as 0.5; if it is 600,000 gallons for the year, report as 0.6; if it is 60,000 gallons for the year, report as 0.6; if it is 60,000 gallons for the year, report as 0.6; if no water is used, tregted, or discharged, report "None." Reasonably accurate estimates are acceptable.

ITEM 1 - Water Intake by kind and source.

A. Include fresh water supplied by a water system (whether publicly or privately owned) whose primary purpose is the supply of water to the general public. Include also fresh water supplied by systems whose principal function is the supply of water to industrial users.

B and C. Include fresh water obtained from your own water supply system and fresh water obtained from another company where the supplying company is not primarily a water supplier to the general public and/or industrial users. Include only your own portion of fresh water obtained from a joint water supply system operated by your company.

E. Report total intake of brackish water (as defined) regardless of source

ITEM 2 - Self-explanatory

ITEM 3 - Water recirculation and rouse.

Report the total quantity of water which would have been needed if no water was recirculated or reused. For example, if 100 million gallons of intake water

were used twice for cooling purposes, and then the same water was a lain reused for washing products or materials, the total water required figure would be 300 million gallons (less consumption and evaporation loss).

ITEM 4 - Water discharged.

Include all water brought to ultimate discharge point for your establishment. Do not include water held is your ponds, leganns, or basins, for reuse or treatment, until actually discharged. Do not report water discharged by evaporation.

A and S - (Self-emplanatory).

C. Ground — include sespage into ground from your halding pands, lageans, etc. (Note: If water is transferred to an agricultural establishment for spray irrigation, report such quantity in 4D).

D. Transferred to other years - include transfers after your own use, to a other establishment of either your company or another company.

ITEMPS - Water Marcel.

Report the total quantity of water treated for control or biological growth, removal of suspended or dissolved solids, for corrosion control, or for any other a purpose by simple or complex methods. From 5A, exclude water intake treated only by shlorination. In 5C, include water treated for discharge by chlorination as well as by other methods. In each section of item 5(A, B, and C), check all applicable methods of treatment.

	·	
Name of person to contest regarding this report	Andrew (Sambar and Artifaction Street, Street,)	Telephone number
Weyerhaeuser Company, Paper Div.	Platemell, Michigan 49080	
	reprinted the property of the same of the	
Loland I Cam Jaman	Nanager Nanager	June 12, 1965

MATERIALS FREP SECTIO:

- 1 Clay Tank Pump Seals 2 #h Air Cooling
- 3 Hose at Kady Mill
- 1-3 Go into Power Plant Sewer

CATER SECTION

- 1 Sewer Flush Line
- 2 Reel Cooling Mater

3-5 MovNo Pumps
6-7 Mash Tank Drains
8 Mater Tank OverFlow
There are Six Hoses, only one was active!